

SPEC SHEET · TAPTECH TAG

TapTech Sticker sheet

An adhesive sticker tag, cut to shape and supplied in sheets, for packaging, glass, walls, print and anything not metal.

STOCK LEAD TIME

1 week

CHIP

Standard or Advance

Specification

SIZE	34 to 150 mm
SHAPE	Circle, square or a custom cut
MATERIAL	Printed face with a scratch-resistant laminate
ADHESIVE	3M permanent adhesive
READ RANGE	To be confirmed
SURFACES	Packaging, glass, painted walls, print, product. Not for metal
WATER	Water resistant
OPERATING TEMP.	To be confirmed
SUPPLIED AS	Sheets

Print

BLEED

3 mm past the trim on every printed edge

SAFE AREA

Text and logos at least 2 mm inside the trim

PRINT

Full colour

FINISH

Crystal matt, smooth matt or gloss laminate

UNIQUE ID OR QR

Available

CUSTOM SHAPES

Supply the cut line as its own layer

Chip options

STANDARD

NXP NTAG213

144 bytes · authenticates the tag

ADVANCE

NXP NTAG424 DNA

416 bytes · encrypted, per-tap authentication

Chip data sheets:
docs.departmnt.xyz/explore/downloads

Durability

SUPPLIER RATING

100,000 taps and 50 years

INDOORS

Made for high-wear indoor use

OUTDOORS

Medium term, 3 to 5 years. Ask for strong sunlight

Good to know

It will not read on metal. Use the on-metal sticker on shelves, lift doors and fridges.

A sticker can be peeled off by anyone. The chip still authenticates the tag.

Artwork

Vector PDF, AI or EPS. Images at least 200 dpi at print size.

CMYK, with a Pantone reference for brand colours. Fonts outlined.

Unique QR codes or IDs: place a sample, and send the data as a spreadsheet.

Start from this format's die-line. Every order is proofed before production.

Die-line and guidelines: docs.departmnt.xyz/explore/ordering-tags