

SPEC SHEET · TAPTECH TAG

TapTech Wristband

A printed PVC plate with the chip inside, on a fabric strap, for entry, zones and crew. Worn, not fixed.

STOCK LEAD TIME

4 weeks

CHIP

Standard or Advance



Specification

PLATE	35.3 x 25.4 mm, rounded rectangle, two strap slots
STRAP	Fabric or PVC, printed, up to 96.5 x 15 mm per repeat
MATERIAL	PVC plate; fabric strap
CLOSURE	Push-button toggle: single use, or adjustable for multi-use
READ RANGE	41 to 50 mm
SURFACES	Worn on the wrist. Not for metal
WATER	Waterproof
OPERATING TEMP.	To be confirmed
SUPPLIED AS	Single units

Print

BLEED

3 mm past the trim on every printed edge

SAFE AREA

Text and logos at least 2 mm inside the trim

PRINT

Full colour, both faces of the plate, and the strap

FINISH

Gloss or matt plate

UNIQUE ID OR QR

Available on either face of the plate

Chip options

STANDARD

NXP NTAG213

144 bytes · authenticates the tag

ADVANCE

NXP NTAG424 DNA

416 bytes · encrypted, per-tap authentication

Chip data sheets:
docs.departmnt.xyz/explore/downloads

Durability

SUPPLIER RATING

100,000 taps and 50 years

USE

Single use or multi-use, depending on the toggle

WEATHER

To be confirmed

Good to know

Also worn as a lanyard: the plate on a cord instead of a strap.

Built for one event. A card or a garment tag keeps the relationship after it.

The plate also comes rounded on request. Sizes are confirmed at proof.

Artwork

Vector PDF, AI or EPS. Images at least 200 dpi at print size.

CMYK, with a Pantone reference for brand colours. Fonts outlined.

Unique QR codes or IDs: place a sample, and send the data as a spreadsheet.

Start from this format's die-line. Every order is proofed before production.

Die-line and guidelines: docs.departmnt.xyz/explore/ordering-tags